

General International Variable Speed "MAXI-LATHE VS+" Wood Lathe Model 25-200

Features:

- Quick lock control levers easily position tool rest
- Stable cast iron frame, head & tailstock to reduce chatter and vibration for smoother turning
- Maximum distance of 17-5/16" between centers
- Maximum distance of 49" between centers with optional bed extension (Item 25-205)
- Quick release lever for quick belt positioning changes
- 3 Variable speed ranges: 300-900, 600-1800 & 1200-3600 RPM
- Digital spindle speed display
- Headstock pivots 360° with 180° positive stop for outboard turning
- Features positive spindle indexing in 10° increments - total 36 index positions
- Accessories included: live center, spur center, knockout bar & safety glasses

Specifications:

Spindle Speeds	300-3600 RPM
Swing Over Bed	12" (304 mm)
Swing Over Tool Rest	9-1/4" (236 mm)
Swing Over Side Bed	19-1/4" (490 mm)
Swing Over Side Tool Rest	16-5/8" (424 mm)
Distance Between Centers	17-5/16" (440 mm)
Spindle Thread	1" - 8 TPI
Tailstock Through Hole	3/8" diameter
Morse Taper	MT#2 (headstock & tailstock)
Self Ejecting Travel	2-1/8" (55 mm)
Tool Rest	6" (152 mm)
Face Plate	3" (80 mm)
Indexing Positions	36 x 10°
Motor	3/4HP, 110V, 8A, 2500 RPM
Weight	146 lbs (66.5 kg)