

General International 14" x 30" Wood Lathe Model 25-300

Features:

- Heavy duty cast iron bed for stability and minimal vibration
- Heavy duty enclosed stand
- Headstock pivots 360° with positive stops at 45°, 90° and 180° for multi-position outboard turning
- Electronic inverter for 2 variable speed ranges: 80-1600 RPM & 150-3750 RPM
- Digital spindle speed (RPM) display
- Quiet, highly efficient, low power consumption motor, with forward or reverse rotation
- Flexible gooseneck style work light
- Includes one 110V-15A socket for onboard accessory use
- 12" tool rest and a 3" face plate included
- Features positive spindle indexing in 10° increments - total 36 index positions

Specifications:

Spindle Speed (variable)	80-1600, 150-3750 RPM
Swing Over Bed	14" (356 mm)
Swing Over Tool Rest	10" (255 mm)
Distance Between Centers	30" (762 mm)
Spindle Thread	1" - 8 TPI
Tailstock Through Hole	3/8" diameter (9.5 mm)
Morse Taper	MT#2 (headstock & tailstock)
Spindle Center Line to Floor	44-1/2" (1130 MM)
Self Ejecting Travel	3" (76 mm)
Headstock Movement	Pivot 45°, 90°, 180° & 360°
Indexing Positions	36 x 10°
Overall Dimensions (lxwxh)	16" x 57" x 47-5/8" (410x1450x1210mm)
Motor	1HP, 220V, 3 Ph, 8A
Weight	308 lbs. (140 kg)