

General International 14" Panel Saw

Model 50-320

Features:

- Independent motor for main blade and scoring blade
- Sturdy outrigger system and rugged two position crosscut fence with dual heavy duty flip up stops
- Large sliding table with anodized aluminum parts for longer life
- Slider features smooth double roller guide construction and mid point and rear locking clamp to lock table in place when slider is not required
- Deluxe Excalibur quick adjust telescopic blade cover with dust extraction capabilities
- Straight line workpiece rip clamp for safer cuts with solid wood boards
- User friendly external scoring blade adjustment
- 0 to 45° left or right crosscut fence adjustment with easy read degree scale for accurate miter cuts
- Magnetic switch with thermal overload protection
- Safety lockout switch in the blade change area to prevent unintentional/unwanted startup
- Heavy duty rip fence system with cast iron main body and all steel guide rail for rock solid positioning

Specifications:

Main Blade/Arbor Diameter	14" (355 mm)/30 mm
Scoring Blade/Arbor Diameter	4-3/4" (120 mm)/20 mm
Arbor Speed	Main: 3000, 4000, 5000 RPM Scoring: 8000 RPM
Arbor Tilt Range	0-45° (to right)
Sliding Table Dimensions	126" x 15-1/2" (3200 x 392 mm)
Main Table Size	21-1/2" x 35-1/4" (548 & 895 mm)
Extension Tables (steel)	Right: 37-3/8" x 35-1/4" (950 x 895 mm) Rear: 12-5/8" x 32-5/8" (320 x 830 mm)
Maximum Length of Cut	126" (3200 mm)

Maximum Rip to Right of Blade	51-1/8" (1300 mm)
Maximum Depth of cut at 90/45°	4-1/8" (105 mm)/3" (76 mm)
Dust Collection Outlets	1x4-3/4" (120 mm) 1x4" (100 mm)
Main Motor M1	5HP, 220V, 1Ph, 25A
Main Motor M2	7.5HP, 220V, 3Ph, 20A
Main Motor M3	7.5HP, 600V, 3Ph, 7.3A
Scoring Motor M1	1HP M1 - 8A M2 - 3.2A M3 - 1.3A
Weight	1892 lbs (860 kg)