

General International 12” Drill Press Model 75-010

Features:

- Forced opening line interrupter switch, requires machine restart in case of power failure or circuit interruption
- Adjustable spindle tension return spring
- Built-in laser pointer
- Sturdy design with cast iron head, base and table
- High quality bearings for smooth vibration free operation
- Simple hand lever controlled mechanical variable speed from 500 to 3000 rpm
- Digital spindle speed display.
- 1/3 HP industrial-quality 120V motor
- Equipped with easy to adjust dual depth stop for complete control of both down stroke depth and upstroke travel
- 5/8" chuck with key & convenient onboard chuck key holder
- Easy to use see through flip up chuck guard included
- Crank operated rack and pinion table height adjustment

Specifications:

Swing	12" (305 mm)
Drilling Capacity	5/8" (16 mm)
Chuck Size	5/8" (16 mm)
Spindle Travel	3-1/8" (80 mm)
Spindle Distance to Table	15" (380 mm)
Spindle Distance to Base	21-7/8" (556 mm)
Table Size	9-1/2" x 9-1/2" (240 x 240 mm)
Column Diameter	2-1/2" (65 mm)
Spindle Speeds (variable)	500-3000 rpm
Spindle Taper	MT2
Overall Height	33" (840 mm)
Base Size	15" x 9-5/8" (380 x 245 mm)
Motor (prewired 110V)	1/3 HP, 120V, 3.1A
Weight	75 lbs (34 kg)

