

General International Electronic Variable Speed Drill Press Model 75-915T

Features:

- Powerful 2HP motor provides plenty of power to suit a wide variety of drilling applications
- Front mounted digital spindle speed display
- Electronic variable speed control adjusts spindle speed from 150 to 3000 RPM
- Large precision ground cast iron table with t-slots for easy setups
- Large mushroom style emergency stop button for quick easy shut-off
- Front mounted positive control depth stop
- Solid head construction for accuracy and rigidity
- Front or side rack and pinion gear assembly table height adjustment
- Timing belt driven transmission to avoid slippage
- Forward/reverse tapping system

Specifications:

Swing	16" (408 mm)
Drilling Capacity	Steel: 1-3/16" (30 mm) Cast Iron: 1-1/4" (32 mm)
Tapping Capacity	Steel: 5/8" (16 mm) Cast Iron: 3/4" (19 mm)
Spindle Taper	MT#3
Spindle Travel	5-9/32" (134 mm)
Quill Dia.	2-7/16" (62 mm)
Column Dia.	3-5/8" (92 mm)
Spindle Nose to Table	26-9/16" (675 mm)
Spindle Nose to Base	44-1/16" (1120 mm)
Table Size	18-1/8" x 14-5/32" (460 x 360 mm)
Table Slots	2 x 1/2" (14 mm)
Base Size	14-3/8" x 21" (365 x 535 mm)
Spindle Speed	150-3000 RPM

Motor	2HP, 220V, 3Ph, 7A
Coolant Motor (optional)	1/8HP
Weight	403 lbs (183 kg)